



SELECT DESIRED FINISH:

- ASH BROWN
- MONTEREY SAND
- ROCKY GREY
- SIDEWALK GREY



DETAIL A



TYPICAL SECTION OF FLOOR

COMPONENTS (APPROX. 80 MILS)

**FLEXSTONE #3 EPOXY PRIMER/ SEALER** - 2:1 MIX (2 PARTS A/ 1 PART B)

**FLEXSTONE TUFF BASE COAT (WHITE)** - 4:1 MIX (4 PARTS BASE/ 1 PART WATER)

**FLEXSTONE AL COLOR COAT** - FADE RESISTANT TOP COAT 1 PART URETHANE (MIX THOROUGHLY BEFORE APPLYING)

- ADD SHURGRIP SLIP-RESISTANT ADDITIVE TO AL TOP COAT OR SPREAD 20-30 GRIT SILICA SAND OVER WET TOP COAT.

MANUFACTURERS NOTES

1. FOR CONCRETE SURFACES, FLEXSTONE #3 PRIMER/SEALER (A+B) MUST BE INSTALLED PRIOR TO THE INSTALLATION OF BASE MEMBRANE AND FINISH COATS.

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT [www.CADdetails.com/info](http://www.CADdetails.com/info) AND ENTER REFERENCE NUMBER 5457-002.

