



SELECT DESIRED FINISH:

- BOREAL BROWN
- BADLANDS TAN
- MOUNTAIN GRANITE
- HUDSON GREY



DETAIL A



TYPICAL SECTION OF FLOOR

COMPONENTS (APPROX. 100 MILS)

**FLEXSTONE #3 EPOXY PRIMER/ SEALER** - 2:1 MIX (2 PARTS A/ 1 PART B)

**FLEXSTONE TUFF BASE COAT (WHITE)** - 4:1 MIX (4 PARTS BASE/ 1 PART WATER)

**FLEXSTONE AR COLOR COAT** - SEALS BASE AND HOLD CHIPS 1 PART URETHANE (MIX THOROUGHLY BEFORE APPLYING)

**FLEXSTONE BLENDED COLOUR FLAKES PRE-MIXED BLENDS** - BROADCAST INTO WET AR COLOUR COAT

**FLEXSTONE CLEAR FINISH COAT**: 1 PART URETHANE (POUR & APPLY)

MANUFACTURERS NOTES

1. FOR CONCRETE SURFACES, FLEXSTONE #3 PRIMER/SEALER (A+B) MUST BE INSTALLED PRIOR TO THE INSTALLATION OF BASE MEMBRANE AND FINISH COATS.

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT [www.CADdetails.com/info](http://www.CADdetails.com/info) AND ENTER REFERENCE NUMBER 5457-001.

