

FSC Aspartic Clear Coat

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations
Revision Date: 01/12/2016 Date of issue: 01/12/2016

Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Name: Specguard SG-SCP20

Product Code: SG-SCP20

1.2. Intended Use of the Product

Use of the substance/mixture: Coating for Marine Products, corrosion, concrete. For professional use only.

1.3. Name, Address, and Telephone of the Responsible Party

Company

Marine Fenders International Inc.

909 Mahar Ave

Wilmington, CA 90744

310-834-7037

www.marinefendersintl.com

1.4. Emergency Telephone Number

Emergency Number : CHEMTREC Within USA and Canada: 1-800-424-9300 CCN709733 or +1-703-527-3887 (collect calls accepted) +1-703-741-5500 (from anywhere in the world)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US classification

Flam. Liq. 3 H226

Acute Tox. 1 (Inhalation:vapor) H330

Skin Corr. 1B H314

Eye Dam. 1 H318

Resp. Sens. 1 H334

Skin Sens. 1 H317

STOT SE 3 H335

Aquatic Acute 3 H402

Aquatic Chronic 3 H412

Full text of hazard classes and H-statements : see section 16

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H226 - Flammable liquid and vapor.
H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H330 - Fatal if inhaled.
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 - May cause respiratory irritation.
H402 - Harmful to aquatic life.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary Statements (GHS-US)

: P210 - Keep away from extremely high or low temperatures, ignition sources, and incompatible materials. - No smoking.
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical, ventilating, and lighting equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe vapors, mist, or spray.
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing must not be allowed out of the workplace.

FSC Aspartic Clear Coat

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, and eye protection.
P284 - In case of inadequate ventilation wear respiratory protection.
P301+P330+P331 - If swallowed: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a poison center or doctor.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P342+P311 - If experiencing respiratory symptoms: Call a poison center or doctor.
P363 - Wash contaminated clothing before reuse.
P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P235+P405 - Keep cool. Store locked up.
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	%	GHS-US classification
Isophorone diisocyanate	(CAS No) 4098-71-9	49	Acute Tox. 1 (Inhalation:dust,mist), H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
Propylene carbonate	(CAS No) 108-32-7	10	Eye Irrit. 2A, H319
Propylene glycol monomethyl ether acetate	(CAS No) 108-65-6	9	Flam. Liq. 3, H226
Glyceryl polypropylene glycol triether	(CAS No) 25791-96-2	9	Not classified
Strontium oxide (SrO)	(CAS No) 1314-11-0	8	Skin Corr. 1B, H314 Eye Dam. 1, H318
Alkanes, C10-13-iso-	(CAS No) 68551-17-7	8	Flam. Liq. 3, H226 Asp. Tox. 1, H304
Iron oxide (Fe ₂ O ₃)	(CAS No) 1309-37-1	4	Comb. Dust
Propylene glycol diamine, 2-amino-, diether with Propylene	(CAS No) 9046-10-0	3	Acute Tox. 3 (Oral), H301 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

FSC Aspartic Clear Coat

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid Measures After Inhalation: First, take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate respiratory protective equipment, use the buddy system), then remove the exposed person to fresh air. Keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

First-aid Measures After Skin Contact: Remove contaminated clothing. Immediately flush skin with plenty of water for at least 60 minutes. Seek medical attention immediately if irritation develops or persists. Wash contaminated clothing before reuse.

First-aid Measures After Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 60 minutes. Immediately call a POISON CENTER or doctor/physician.

First-aid Measures After Ingestion: Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/Injuries: Fatal if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Causes severe skin burns and eye damage. May cause an allergic skin reaction.

Symptoms/Injuries After Inhalation: Fatal if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Symptoms may include: Cough, headache, sore throat, or unconsciousness. Inhalation of this material can cause serious health effects in small amounts, leading to unconsciousness and death. May cause respiratory irritation.

Symptoms/Injuries After Skin Contact: Corrosive. Causes burns. May cause an allergic skin reaction. Symptoms may include: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact: Causes serious eye damage. Symptoms may include: Redness, pain, swelling, itching, burning, tearing, and blurred vision. Causes permanent damage to the cornea, iris, or conjunctiva.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, dry chemical, alcohol foam, carbon dioxide.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Flammable liquid and vapor.

Explosion Hazard: May form flammable/explosive vapor-air mixture.

Reactivity: Reacts with (strong) oxidizers: (increased) risk of fire.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.

Other Information: Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Use special care to avoid static electric charges. Keep away from heat, sparks, open flames, hot surfaces. No smoking. Avoid all contact with skin, eyes, or clothing. Avoid breathing (vapor, mist, spray).

6.1.1. For Non-emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

6.2. Environmental Precautions

Avoid release to the environment.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Ventilate area. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

FSC Aspartic Clear Coat

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methods for Cleaning Up: Warning - toxic vapors and mist may be present. Stop the source of the release, if safe to do so. Check air quality before entering area. Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools. Clean up spills immediately and dispose of waste safely.

6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable. When heated, material emits irritating fumes. Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained.

Precautions for Safe Handling: Avoid contact with skin and eyes. Take precautionary measures against static discharge. Use only non-sparking tools. Keep away from heat, sparks, open flames, hot surfaces. No smoking.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, lighting, ventilating equipment.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Store locked up. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

7.3. Specific End Use(s)

Coating for Marine Products, corrosion, concrete. For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Isophorone diisocyanate (4098-71-9)		
USA ACGIH	ACGIH TWA (ppm)	0.005 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	0.045 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	0.005 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	0.180 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	0.02 ppm
Propylene glycol monomethyl ether acetate (108-65-6)		
USA AIHA	WEEL TWA (ppm)	50 ppm
Iron oxide (Fe ₂ O ₃) (1309-37-1)		
USA ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ (respirable fraction)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³ (dust and fume)
USA IDLH	US IDLH (mg/m ³)	2500 mg/m ³ (dust and fume)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	10 mg/m ³ (fume) 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)

8.2. Exposure Controls

Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Local exhaust and general ventilation must be adequate to meet exposure standards. Site-specific risk assessments should be conducted to determine the appropriate exposure control measures. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. Gas detectors should be used when toxic and flammable gases/vapor may be released. Ensure all national/local regulations are observed.

FSC Aspartic Clear Coat

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing

: Corrosion-proof clothing. Wear fire/flammable resistant/retardant clothing.

Hand Protection

: Wear chemically resistant protective gloves.

Eye Protection

: Chemical safety goggles and face shield.

Skin and Body Protection

: Wear suitable protective clothing.

Respiratory Protection

: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear a self-contained breathing apparatus (SCBA).

Environmental Exposure Controls

: Do not allow the product to be released into the environment.

Consumer Exposure Controls

: Do not eat, drink or smoke during use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: No data available
Odor	: No data available
Odor Threshold	: No data available
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: No data available
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20 °C	: No data available
Relative Density	: No data available
Solubility	: No data available
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available

9.2. Other Information

No additional information available

SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Reacts with (strong) oxidizers: (increased) risk of fire.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Incompatible materials. Ignition sources.
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers. Amines. Alkalis. Alcohols. Water.
- 10.6. Hazardous Decomposition Products:** Thermal decomposition generates: Carbon oxides (CO, CO₂). Nitrogen oxides. Isocyanate containing vapors.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information On Toxicological Effects

Acute Toxicity: Inhalation:vapour: Fatal if inhaled.

Specguard SG-SCP20	
ATE (Vapors)	0.28 mg/l/4h

FSC Aspartic Clear Coat

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Isophorone diisocyanate (4098-71-9)	
LD50 Dermal Rabbit	1060 - 4780 mg/kg
LC50 Inhalation Rat	0.135 mg/l/4h
LC50 Inhalation Rat	0.031 mg/l/4h
ATE (Vapors)	0.14 mg/l/4h
ATE (Dust/Mist)	0.03 mg/l/4h
Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)	
LD50 Oral Rat	242 mg/kg
Propylene glycol monomethyl ether acetate (108-65-6)	
LD50 Oral Rat	8532 mg/kg
LD50 Dermal Rabbit	> 5 g/kg
Glyceryl polypropylene glycol triether (25791-96-2)	
LD50 Oral Rat	> 64 ml/kg
LD50 Dermal Rabbit	> 20 ml/kg
Propylene carbonate (108-32-7)	
LD50 Oral Rat	29000 mg/kg
LD50 Dermal Rabbit	> 20 ml/kg
Iron oxide (Fe₂O₃) (1309-37-1)	
LD50 Oral Rat	> 10000 mg/kg

Skin Corrosion/Irritation: Causes severe skin burns and eye damage.

Serious Eye Damage/Irritation: Causes serious eye damage.

Respiratory or Skin Sensitization: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Iron oxide (Fe₂O₃) (1309-37-1)	
IARC group	3

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): May cause respiratory irritation.

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Fatal if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Symptoms may include: Cough, headache, sore throat, or unconsciousness. Inhalation of this material can cause serious health effects in small amounts, leading to unconsciousness and death. May cause respiratory irritation.

Symptoms/Injuries After Skin Contact: Corrosive. Causes burns. May cause an allergic skin reaction. Symptoms may include: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact: Causes serious eye damage. Symptoms may include: Redness, pain, swelling, itching, burning, tearing, and blurred vision. Causes permanent damage to the cornea, iris, or conjunctiva.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Isophorone diisocyanate (4098-71-9)	
EC50 Daphnia 1	83.7 mg/l
Propylene glycol monomethyl ether acetate (108-65-6)	
LC50 Fish 1	161 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	> 500 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Propylene carbonate (108-32-7)	
LC50 Fish 1	> 1000 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])
EC50 Daphnia 1	> 500 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and Degradability No additional information available

FSC Aspartic Clear Coat

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative Potential

Propylene glycol monomethyl ether acetate (108-65-6)	
Log Pow	0.43
Propylene carbonate (108-32-7)	
Log Pow	0.48 (at 25 °C)

12.4. Mobility in Soil No additional information available

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Sewage Disposal Recommendations: This material is harmful to the aquatic environment. Keep out of sewers and waterways.

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

Additional Information: Handle empty containers with care because residual product is flammable. Container may remain hazardous when empty. Continue to observe all precautions.

SECTION 14: TRANSPORT INFORMATION

14.1. In Accordance with DOT

Proper Shipping Name : CORROSIVE LIQUIDS, FLAMMABLE, N.O.S. (Strontium oxide, Propylene glycol monomethyl ether acetate; Alkanes, C10-13-iso-)

Hazard Class : 8

Identification Number : UN2920

Label Codes : 8, 3

Packing Group : II

ERG Number : 132



14.2. In Accordance with IMDG

Proper Shipping Name : CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Strontium oxide, Propylene glycol monomethyl ether acetate; Alkanes, C10-13-iso-)

Hazard Class : 8

Subsidiary Risk(s) : 3

Identification Number : UN2920

Packing Group : II

Label Codes : 8, 3

EmS-No. (Fire) : F-E

EmS-No. (Spillage) : S-C



14.3. In Accordance with IATA

Proper Shipping Name : CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Strontium oxide, Propylene glycol monomethyl ether acetate; Alkanes, C10-13-iso-)

Packing Group : II

Identification Number : UN2920

Hazard Class : 8

Label Codes : 8, 3

Subsidiary Risk(s) : 3

ERG Code (IATA) : 8F



SECTION 15: REGULATORY INFORMATION

15.1 US Federal Regulations

Specguard SG-SCP20	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard
Isophorone diisocyanate (4098-71-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on the United States SARA Section 302 Subject to reporting requirements of United States SARA Section 313	
SARA Section 302 Threshold Planning Quantity (TPQ)	500
SARA Section 313 - Emission Reporting	1.0 %

FSC Aspartic Clear Coat

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Propylene glycol monomethyl ether acetate (108-65-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Fire hazard
Glyceryl polypropylene glycol triether (25791-96-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Propylene carbonate (108-32-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Strontium oxide (SrO) (1314-11-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Iron oxide (Fe₂O₃) (1309-37-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Alkanes, C10-13-iso- (68551-17-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2 US State Regulations

Isophorone diisocyanate (4098-71-9)
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List
Iron oxide (Fe₂O₃) (1309-37-1)
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date	: 01/12/2016
Other Information	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 1 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 1
Acute Tox. 1 (Inhalation:vapor)	Acute toxicity (inhalation:vapor) Category 1
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Comb. Dust	Combustible Dust
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 3	Flammable liquids Category 3
Resp. Sens. 1	Respiratory sensitisation Category 1
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Sens. 1	Skin sensitization Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
	May form combustible dust concentrations in air
H301	Toxic if swallowed
H304	May be fatal if swallowed and enters airways
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction

FSC Aspartic Clear Coat

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H318	Causes serious eye damage
H319	Causes serious eye irritation
H330	Fatal if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)